


+WDM



IWDM , 1550/1480WDM 980/1550WDM .

-
-
-

-
- CATV
-

- Telcordia GR-1221-CORE
- RoHS

		1550/980	1550/1480	nm
		1528~1569	1528~1563	nm
		965~990	1450~1495	nm
		≤0.9	≤1.0	dB
		≤0.55	≤0.55	dB
		≥21	≥36	dB
		≥14	≥14	dB
		≥45		dB
		≤0.5		dB
		≤0.15		dB
		≤0.05(PMD), ≤0.10()		dB
		≥50		dB

	≤300	mw
	-5~70	
	-40~85	
	Φ5.2x32(Normal);Φ3.5x29(Mini); Φ3.0x18(Mini)	mm

IWDM- □-□-□-□-□-□-□-□

Package NA: Φ 5.2*32mm;Mini: Φ 3.5*29mm

Connectors:FC/UPC,SC/UPC,LC/UPC,00:No Connector

Fiber Length 1 1.0m; customer specify

Fiber Dia. 09 Φ 0.9mm 025: Φ 0.25mm; customer specify

Type PIS:Single;PID:Dual ;PISL: Low PMD,Single

Pump Location A:Pump before ISO;B:Pump after ISO

Wavelength 095:980/1550;145:1480/1550